



oakdale
timber

**TASMANIAN OAK:
Elegant & durable**

Warm, enduring, sustainable

Nothing compares to the strength and exceptional beauty of Tasmanian Oak

Tasmanian Oak is known locally and internationally as a durable, resilient and attractive timber. The strength and natural beauty of this hardwood timber provides quality that will endure the test of time. Versatile and contemporary, Tasmanian Oak is a favourite with architects and builders looking to inject a modern, fresh look to their projects.

Style and function

This robust timber has a wide range of applications to suit commercial or residential projects, from cladding, internal panelling, joinery and mouldings, to flooring (T&G strip, overlay and parquet). Find your perfect fit with standard or customised profiles.

Available in four grades and finishes, Tasmanian Oak showcases the beauty and rich character of natural timber. Choose from Feature, Standard, Select or Rustic grades to ensure you achieve the look you are after.

Easy to install and care for, this hard wearing timber stains well and polishes to an impressive finish.



Environmentally Friendly

Bring the timeless elegance of timber into your build with peace of mind that this renewable resource is responsibly and sustainably sourced from Tasmanian forest timbers. We hold Fine Timber Tasmania Chain of Custody accreditation which complies with Australian Forestry Standard and PEFC certification.

Socially Responsible

Oakdale Industries has been a trusted manufacturer of quality timber products since 1964. We know timber, and pride ourselves on providing genuine, personal customer service. By purchasing our products you are supporting a social enterprise that trains and employs more than 30 people with a disability.

Specifications

COMMON NAME	Tasmanian Oak consisting of three similar species of eucalypt hardwoods grouped collectively
BOTANICAL NAME	E. delegatensis, E. regnans and E. obliqua
COLOUR	Light, varying from straw to reddish brown with intermediate shades of cream and pink
GRAIN	Straight, open and even, occasionally coarse grained or fiddlebacked. Growth Rings are visible
DENSITY	700 kg/m ³ at a 12% moisture content, unseasoned approximately 1000kg m ³
HARDNESS (JANKA)	4.2 kN unseasoned, 5.7kN seasoned
BOARD DURABILITY	Class 4 (in-ground) Class 3 (Outside above ground)

BOARD SIZE

DRESSED SEASONED	40 to 285mm wide by 12 to 42mm thick
UNDRESSED SEASONED	50 to 300mm wide by 19 to 50mm thick. Lengths up to 5400mm long are available, with the bulk of production between 2700 and 4200mm long

For further information and specifications, please visit www.tastimber.gov.au

Product inquiries

t 1300 042 042 e timber@oakdale.org.au

Visit our showroom to see how we can bring your vision to reality at 80 Flagstaff Gully Link Road, Warrane, Tasmania.

oakdale.org.au

Oak Tasmania trading as Oakdale Timber ABN 44 055 920 306, August 2018

oakdale
timber

